

SPAN CLASSES	
Use these classes to set the <b>width</b> of a column	
.span-1	.span-13
.span-2	.span-14
.span-3	.span-15
.span-4	.span-16
.span-5	.span-17
.span-6	.span-18
.span-7	.span-19
.span-8	.span-20
.span-9	.span-21
.span-10	.span-22
.span-11	.span-23
.span-12	.span-24



# blueprintcss

spend your time innovating, not replicating.

version 1.0

Blueprint CSS version 1.0 ([www.blueprintcss.org](http://www.blueprintcss.org))

Copyright © 2007-2011 blueprintcss.org

Cheat sheet v.4.2 by Gareth J M Saunders ([www.garethjmsaunders.co.uk/blueprint](http://www.garethjmsaunders.co.uk/blueprint))

APPEND CLASSES	
Add these to a column to add empty columns to the <b>right</b> .	
.append-1	.append-13
.append-2	.append-14
.append-3	.append-15
.append-4	.append-16
.append-5	.append-17
.append-6	.append-18
.append-7	.append-19
.append-8	.append-20
.append-9	.append-21
.append-10	.append-22
.append-11	.append-23
.append-12	


PREPEND CLASSES	
Add these to a column to add empty columns to the <b>left</b> .	
.prepend-1	.prepend-13
.prepend-2	.prepend-14
.prepend-3	.prepend-15
.prepend-4	.prepend-16
.prepend-5	.prepend-17
.prepend-6	.prepend-18
.prepend-7	.prepend-19
.prepend-8	.prepend-20
.prepend-9	.prepend-21
.prepend-10	.prepend-22
.prepend-11	.prepend-23
.prepend-12	

VERTICAL CLASSES	
Use these classes on an element to add vertical space.	
.prepend-top	mT 1.5em
.append-bottom	mB 1.5em

PUSH/PULL CLASSES	
Use these classes on an element to <b>push</b> it right into the next column, or <b>pull</b> it left into the previous column.	
.push-1 to .push-24	
.pull-1 to .pull-24	

USAGE	
<body>	<div class="container">
	<div class="span-16">
	<p>Column 1</p>
	</div>
	<div class="span-8 last">
	<p>Column 2</p>
	</div>
	</div>
	</body>
.span-x	implies a column (although .column may still be used). Remember to use ".last" for the last column of the row to avoid it jumping to the next row. Columns may be nested inside one another.

TYPOGRAPHY	
<b>typography.css</b>	sets up some sensible default typography. The <b>font-size</b> percentage is of 16px (0.75 x 16px = 12px). Line-heights and vertical margins are automatically calculated from this in ems.
The base <b>line-height</b> is 18px (1.5em). This means that each element, from line-heights to images has a height that is a multiple of 18 (or 1.5 if you use ems). (See page 2 for a table of values.)	<b>h1-h6</b> color is #111 (nearly black); body <b>color</b> is #222 (dark grey); <b>font-family</b> is "Helvetica Neue", "Helvetica", "Arial", sans-serif.



GRID CLASSES	
.append-x	Add these to a column to add empty columns to the right; x = 1 to 23.
.append-bottom	Add a 1.5em gutter below an element.
.border	Shows a border (#ddd mid-grey) on the right hand side of a column.
.box	Creates a blue padded box inside a column (padding and margin-bottom: 1.5em).
.clear	Regular clearing: apply to a column that should drop below previous ones.
.clearfix	Clearing floats without extra mark-up. (See <a href="http://tinyurl.com/dh352">http://tinyurl.com/dh352</a> )
.colborder	Spans one column with a border in the centre. (#ddd mid-grey)
.column	Use with .span-x classes to create combinations of columns in the layout.
.container	Group your columns within containers; use on <div>. (width: 950px; margin: 0;)
.even	Table-striping for older browsers that don't support 'tbody tr:nth-child(even) td'.
.last	The last column in a row needs this class.
.prepend-x	Add these to a column to add empty columns to the left; x = 1 to 23.
.prepend-top	Add a 1.5em gutter above an element.
.pull-x	Use these classes on an element to pull it left into the previous column; x = 1 to 24.
.push-x	Use these classes on an element to push it right into the next column; x = 1 to 24.
.showgrid	Use this on any .span / .container to see 'grid.png' as a background image.
hr.space	Use this to create a transparent horizontal rule across a column; also use <hr />.
.span-x	Use these classes to set the width of a column; x = 1 to 24; usually used on a div element. Can also be used on input and textarea elements (uses different widths).

RESET	
Defined mostly in <b>reset.css</b> . Blueprint CSS resets all browsers' default elements including HTML5 to:	<ul style="list-style-type: none"> <li>margin, padding, border: 0</li> <li>font-size: 100.01%</li> <li>font-weight: normal</li> <li>line-height: 1.5</li> <li>other font values: inherit</li> <li>image borders: 0</li> <li>:focus outline: 0</li> </ul> <p>Note that tables will still need cellspacing="0" in the HTML mark-up though.</p>

TYPOGRAPHY CLASSES	
These classes are defined in the <b>typography.css</b> file. Other typographic elements are also defined in this file.	
.added	bg #060 (green)
.bottom	mB 0; pB 0
.first	mL 0; pL 0
.hide	display: none
.highlight	bg #ff0 (yellow)
.large	1.2em; line 2.5
.last	mR 0; pR 0
.loud	color #000 (black)
.quiet	color #666 (grey)
.removed	bg #900 (red)
.small	0.8em; line 1.875
.top	mT 0; pT 0

FLOAT CLASSES	
.left	float: left
.right	float: right
p .left/.right	margin:1.5em 1.5em 1.5em 0
FORMS	
.alert	red frame box
.error	red frame box
.info	blue frame box
.notice	yellow frame box
.success	green frame box
fieldset	p, m and border
form.inline	line-height 3
input.text	w 300px p 5px
input.title	font-size 1.5em
input [type=text]	
input [type=password]	
label	bold
legend	m, font 1.2em
select	border 1px
textarea	w390px h250px

IE FIXES	
IE ALL	Alignment of inline forms; margin bugs; fieldset padding (inc. IE8); image resizing; sub/sup line-height.
IE5	Centre layout.
IE6	Legend, label, textarea.
IE6 & IE7	ol numbers and hr margins.
IE7	Code wrap.

