

user manual



Joomla!™
Template



Solidarity

Solidarity v1.0 - Manual v1.0

bonusthemes.com

EXTREME JOOMLA TEMPLATING

Table of Contents

1. Introduction	3
2. General information	3
2.1. Required software	3
2.2. Browser compatibility	3
3. Template installation	4
4. Layout	5
4.1. Template map	6
4.2. CSS structure	7
4.3. Module Suffixes	8
5.1. Logo setup	10
5.2. Banner setup	10
5.3. How to show/hide the BonusThemes logo	10
5.4. PNG fix	10
5.5. How to enable/disable CMenu	11
5.6. How to set the Joomla menu for CMenu	11
5.7. How to enable/disable the SEOCP feature	11
5.8. Hidden module positions	11
5.9. Custom menu styling	12
5.10. How to set the width of any position	12
5.11. How to connect CMenu with the Joomla! content	13
5.12. How to connect CMenu with VirtueMart 1.1	14
5.13. How to set up the article date style	15
5.14. How to set up the styling of the first word of the module titles	15
5.15. How to set up the modules in the positions "top1", "top2" and "top3"	16
Appendix A – How to install a template	17
Appendix B – How to setup a module	20
Appendix C - CMenu to Joomla! content link reference	22
C.1. articles	22
C.2. latest	23
C.3. random	24
C.4. selected	25
Appendix D - CMenu to VirtueMart 1.1 link reference	26
D.1. category	26
D.2. subcategory	27
D.3. featured	28
D.4. latest	28
D.5. random	29
D.6. selected	29
D.7. topten	30

1. Introduction

Solidarity is the October 2009 Joomla! template from BonusThemes.com.

Solidarity is a template built with warm colors and a way to inspirit the notions of peace, security and hope. Solidarity is meant to work for charity and religious oriented websites, but a capable webmaster can use its technologies to make it work for many other types of content like a blog or a presentation type website.

The template features a 3 column layout, plenty of module positions, a menu with built-in support for VirtueMart 1.1, Joomla! articles, native or blog styled date tag for articles, content optimization settings for search engines and significant configuration flexibility for webmasters.

Read the following sections to find detailed information and illustrated examples that explain the ways you can use the template.

2. General information

2.1. Required software

Solidarity works with Joomla! 1.5.x and it is recommended to use the latest version available.

Visit <http://www.joomla.org> to find which is the latest available version for Joomla!. If you are not sure which version you are using at the moment, login to the administrator control panel and locate the version number on the top right corner of the page.

2.2. Browser compatibility

Solidarity is compatible with:

- Firefox 3.5
- Firefox 3
- Safari 4
- Safari 3
- Chrome 2
- Chrome 1
- MS Internet Explorer 8
- MS Internet Explorer 7
- MS Internet Explorer 6

3. *Template installation*

To install the template you can use the Joomla! installation mechanism:

`Extensions > Install/Uninstall`

Alternatively, you may unpack the template in the /template directory.

To activate the template go to

`Extensions > Template Manager`

select the template and click the “Default” button.

Read Appendix A for illustrated examples on how to install and activate a template.

4. Layout

The layout of Solidarity provides 20 regular module positions and 5 invisible positions for supplementary services.

Solidarity implements a technology that makes it really easy to set the width of any position or the main body. Read section 5.10 for more information.

This template uses a collapsible module technology. That makes some positions disappear if there are no published modules in them. This feature gives you the capability to make arrangements for wider space in your pages.


On the top of its layout, Solidarity uses CMenus, a menu script that uses a regular Joomla menu as a data source. You have the option of disabling this menu and have a regular module position in its place. This can be set from the Template Manager and the name of the position that replaces CMenus is "header". Read sections 5.5 and 5.6 for more information.

CMenus can also be easily connected with articles from the Joomla! content and VirtueMart's products and categories. Read section 5.11 and Appendix C and for more details on the connection to Joomla! content and section 5.12 and Appendix D for the connection to VirtueMart 1.1.

With this template you have the option to change the way dates for articles appear and give them blog styled date tags. Read section 5.13 for more information.

Solidarity by default differentiates the styling of the first word of your module titles. Read section 5.14 to see how to control this feature.

4.1. Template map



Map of regular module positions for the template Solidarity.

Solidarity also supports 5 hidden positions for supplementary services. Read section 5.8 for more information.

An alternative way to see this map on your website is to use the URI parameter `tp=1`. For example, if your website is "example.com" you can see the template positions by typing <http://www.example.com/?tp=1>

4.2. CSS structure

Solidarity uses the main Joomla template CSS file for typography and other general styling. That main file is `/templates/bt_solidarity/css/template.css`

The file `/templates/bt_solidarity/css/layout.css` contains CSS definitions that control the layout.

The file `/templates/bt_solidarity/css/cmenu.css` contains CSS definitions that control the layout of CMenus, the script for the menu on the top area.

The file `/templates/bt_solidarity/css/table_viewer.css` contains CSS definitions for the "Table" viewer of the photo gallery component Photo Spot.

Naming system for module positions:

The IDs of the `<div>` tags that wrap the template positions always start with "pos_". For example the module position "left" takes the id "pos_left".

4.3. Module Suffixes

There are 5 module styles (or module suffixes) that match the styling of the template.

Sample title

Lorem ipsum dolor sit amet, consectetur adipisicing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat.

mstyle1

Use it only for modules in the position “top1”

Sample title

Lorem ipsum dolor sit amet, consectetur adipisicing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat.

mstyle2

Use it only for modules in the position “top2”

Sample title

Lorem ipsum dolor sit amet, consectetur adipisicing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat.

mstyle3

Use it only for modules in the position “top3”

Sample title

Lorem ipsum dolor sit amet, consectetur adipisicing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua.

Sample title

Lorem ipsum dolor sit amet, consectetur adipisicing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua.

Sample title

Lorem ipsum dolor sit amet, consectetur adipisicing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua.

Sample title

Lorem ipsum dolor sit amet, consectetur adipisicing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua.

Sample title

Lorem ipsum dolor sit amet, consectetur adipisicing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua.

mstyle4u (*)

Use it for modules in the start of a group

mstyle4 (*)

Use it for modules in the middle of a group

mstyle4d (*)

Use it for modules in the ending of a group

mstyle4ud (*)

Use it for independent modules which should have a group start and end

(*) There are four variations of mstyle4. The suffix "u" stands for "up" and "d" for "down. You can use these variations to make a group of modules appear as a unified module.

mstyle5

Does not have any visual styling apart from putting a gap underneath it

5. Template setup

5.1. Logo setup

To setup your logo, publish a “Custom HTML” module with an uploaded image in any template position.

Example:

1. Upload your logo on your website
2. Create a new “Custom HTML” module that contains the URL of the image you just uploaded
3. Publish that module in a suitable position

For additional help with illustrated examples, visit <http://www.bonusthemes.com> and open the tutorial “How to upload your logo” from the tutorials section.

You can publish your logo in any position, but the recommended one for logos is “icon”. If you decide to publish your logo in the position “cpanel”, “icon” or “logo” the height should be 100 pixels.

5.2. Banner setup

To setup a banner, publish a banner module in any template position.

5.3. How to show/hide the BonusThemes logo

You can show or hide the BonusThemes logo from

[Extensions > Template Manger](#)

5.4. PNG fix

MS Internet Explorer 5 and 6 have trouble rendering the alpha levels (transparencies) of PNG images. The template is equipped with a script that fixes this problem. To enable transparencies in PNG files for MS Internet Explorer 5 and 6, use the CSS class “pngfix”. In some cases images appear distorted. To avoid this distortion provide “width” and “height” attributes in your `` HTML tags. Alternatively, you can try the CSS class “pngfix_static”.

HTML example that shows an image tag with pngfix enabled:

```

```

PNG fix’s website:

<http://www.twinhelix.com>

5.5. How to enable/disable CMenu

CMenu (Classic Menu) is the menu that appears on the top of the page.

If you want to use a module instead of CMenu you can disable it from

[Extensions > Template Manager](#)

locate the option "Header Menu Type" and set it to "Position Header". You can now publish your module in the position "header".

5.6. How to set the Joomla menu for CMenu

CMenu by default shows the contents of the Joomla menu "topmenu".

In order to change the source of CMenu, go to

[Extensions > Template Manager](#)

and use the option "Header Menu Name".

5.7. How to enable/disable the SEOCP feature

SEOCP (Search Engine Optimization Content Positioning) is a feature that controls the position of the main content of the pages.

When SEOCP is enabled the content is internally positioned on the top of the HTML code and this helps search engines find and analyze the content easier. When the page loads, a JavaScript script moves the content to the proper position so that the visual structures can display it in the way the human eye can understand better.

SEOCP needs JavaScript to work. This means that users with JavaScript disabled will not be able to read the content of the page.

By default, SEOCP is disabled. To enable SEOCP go to

[Extensions > Template Manager](#)

and use the option "SEOCP".

5.8. Hidden module positions

Solidarity features 5 hidden positions for supplementary functionality. The names of these positions are "aux1", "aux2", "aux3", "aux4", "aux5".

The IDs of the container HTML elements for these positions are "pos_aux1", "pos_aux2", "pos_aux3", "pos_aux4" and "pos_aux5" respectively.

5.9. Custom menu styling

The Solidarity template has a default way of laying out menus. It uses a specific set of CSS rules that may not appear nice in exception cases. One such exception is a horizontal menu.

To make the template ignore the default layout for menus you can use a custom “Menu Class Suffix”. This should not be confused with “Module Class Suffix”. From the administrator’s control panel go to

`Extensions > Module Manager`

open the menu module that needs to have a different layout, open the “Advanced Parameters” panel on the right side of the page and set the “Menu Class Suffix” to any value (type for example “mystyle”) and click the “Save” button.

Solidarity also contains a secondary styling for menus. To use it follow the instructions above and type “menu1” in the “Menu Class Suffix” input box.

5.10. How to set the width of any position

To set the width of a module position in the template go to

`Extensions > Template Manager`

click the `bt_solidarity` template and use the “Position widths” text box.

You can simply type the name of the template, a colon (:) and a width in pixels. Each line should have one setting.

Example:

`left: 160`

`right: 200`

To set the width of the main body use the keyword: “mainbody”.

Example:

`mainbody: 700`

5.11. How to connect CMenu with the Joomla! content

CMenu is the menu that appears by default as the main template menu. As explained in previous sections its data source is a regular Joomla! menu of your choice.

The connection of CMenu with the Joomla! content is a very simple task. All you have to do is create an "External Link" menu item and use the "Link" text box to define the type of connection you want. The system will convert your link to the Joomla! content if it starts with ":cnt:". After that keyword, you should enter a type of connection and optional parameters.



Here is an example of what the Link should look like if you want to show links from all the Joomla! content under a menu item:

```
:cnt:articles
```


Now lets narrow the results to show links of articles in a specified category. Lets pick the category with ID 1 for our example.

```
:cnt:articles:cat=1
```

Depending on the command you use ("articles" in this case) you have optional parameters to filter your connection. For example, you may want to show a maximum of 20 links. To do that, you should use the parameter "max":

```
:cnt:articles:cat=1:max=20
```

The colon (:) symbol is a delimiter for your parameters. If you want to use parameters, you should separate them with a colon (:).



Item Details

Title:	Articles
Alias:	
Link:	:cnt:articles:cat=1
Display in:	Top Menu
Parent Item:	Top

Top
About Joomla!
Features
- test 1
- test 222 dskfi sdalfi sdlfisda

Here is a list with all the available commands:

- articles: Displays article links in the order set from the control panel.
- latest: Displays article links putting the newer ones first.
- random: Displays article links in random order.
- selected: Displays selected article links.

Read Appendix C for a detailed reference on the commands and their parameters.

5.12. How to connect CMenus with VirtueMart 1.1

CMenus may also use VirtueMart as a data source for menu items.

The connection of CMenus with VirtueMart 1.1 is as easy as the connection to the Joomla! content explained in the previous section. All you have to do is create an "External Link" menu item and use the "Link" text box to define the type of connection you want. The system will convert your link to VirtueMart data if it starts with ":vm:". After that keyword, you should enter a type of connection and optional parameters.



Here is an example of what the Link should look like if you want to show all the VirtueMart categories under a menu item:

```
:vm:subcategory
```


And here is a more complex example that connects a menu item with the sub-categories of the category 5.

```
:vm:subcategory:id=5
```

Depending on the command you use ("category" in this case) you have optional parameters to filter your connection. For example, you may want to show only one level of sub-categories. To do that, you should use the parameter "depth":

```
:vm:subcategory:id=5:depth=1
```

The colon (:) symbol is a delimiter for your parameters. If you want to use parameters, you should separate them with a colon (:).



Item Details

Title:	Products
Alias:	
Link:	:vm:category
Display in:	Top Menu
Parent Item:	Top

Here is a list with all the available commands:

- category: Displays VirtueMart product categories and their sub-categories.
- subcategory: Displays VirtueMart sub-categories.
- featured: Displays featured products.
- latest: Displays latest products.
- random: Displays random products.
- selected: Displays selected products.
- topten: Displays best selling products.

Read Appendix D for a detailed reference on the commands and their parameters.

5.13. How to set up the article date style

Solidarity provides two ways to display dates for articles:

Native



The screenshot shows a Joomla! Community Portal page. At the top, it says "Joomla! Community Portal". Below that, there's a user profile icon followed by "Written by Administrator" and a clock icon followed by "Saturday, 07 July 2007 09:54". The main content area contains text about the Joomla! Community Portal and a link to the Joomla! User Group. At the bottom, there's a link to the Joomla! Community Magazine.

Blog



The screenshot shows a Joomla! Community Portal page with a blog-style date display. On the left, there's a small calendar icon with "Jul" at the top and "7" in the center, indicating the date is July 7th. The rest of the page structure is identical to the native date display screenshot above, including the title, author information, and content links.

To set the article date style of the template go to

[Extensions > Template Manager](#)

click the `bt_solidarity` template and use the "Article Date Style" drop down box.

5.14. How to set up the styling of the first word of the module titles

With the Solidarity template you can make the template set a differentiated styling for the first word of a module's title.

To control this functionality go to

[Extensions > Template Manager](#)

click the `bt_solidarity` template and use the "Module word" buttons to enable or disable it.

5.15. How to set up the modules in the positions “top1”, “top2” and “top3”

The modules in the positions “top1”, “top2” and “top3” have a predefined background. In order to make your module styling match this background you should assign the module suffixes “mstyle1”, “mstyle2” and “mstyle3”.

Set the module suffix “mstyle1” to the modules in the position “top1”, set “mstyle2” for the modules in the position “top2” and “mstyle3” for the modules in the position “top3”.

You may also want to read section 4.3 to see how these module styles look.

Appendix A – How to install a template

To install a template in Joomla! 1.5.x follow the next 6 steps:


Step 1

Get into the administrator's control panel with your browser.

The URL usually looks like


<http://www.example.com/administrator/>

Step 2




Go to the menu **Extensions > Install/Uninstall**

Step 3


 A screenshot of the Joomla! Extension Manager. At the top, there is a header with a logo and the title 'Extension Manager'. Below the header is a navigation bar with tabs: 'Install' (which is highlighted in blue), 'Components', 'Modules', 'Plugins', 'Languages', and 'Templates'. Under the 'Install' tab, there is a section titled 'Upload Package File' with a 'Package File:' input field, a 'Browse...' button, and a 'Upload File & Install' button. Below this section is another button labeled 'Install from Directory'.

Click the Browse button to find the archive of the template, and then click Upload File & Install to perform the installation procedure.

Step 4




The screenshot shows the Joomla! Extension Manager interface. At the top, there's a navigation bar with links for Install, Components, Modules, Plugins, Languages, and Templates. Below this, a blue header bar displays the message "Install Template Success". The main content area contains a success message: "Easygate is the August 2008 Joomla! template for the registered members of the bonusthemes.com community. Visit <http://www.bonusthemes.com> for more information and support." Below this message is a form titled "Upload Package File" with a "Browse..." button and a "Upload File & Install" button.

Joomla!™ template

If the installation was successful you will be able to see a success message like the one in the image.

Step 5




The screenshot shows the Joomla! Admin Panel. The top navigation bar has tabs for Content, Components, Extensions, Tools, and Help. The "Extensions" tab is currently selected. A dropdown menu is open under the Extensions tab, showing options: Install/Uninstall, Module Manager, Plugin Manager, Template Manager (which is highlighted with a mouse cursor), and Language Manager.

The next thing to do is to activate the template.

Go to Extensions > Template Manager

user manual

Step 6



The screenshot shows the Joomla! Template Manager page. At the top, there's a navigation bar with links for Site, Menus, Content, Components, Extensions, Tools, and Help. On the far right of the header are icons for Preview, Logout, and other site management tools. Below the header, the title 'Template Manager' is displayed above a table. The table has columns for #, Template Name, Default, Assigned, Version, Date, and Author. There are four rows of data:

#	Template Name	Default	Assigned	Version	Date	Author
1	beez			1.0.0	19 February 2007	Angie Radtke/Robert Deutz
2	bt_easygate			1.0	August 2008	BonusThemes.com
3	JA_Purity	★		1.2.0	12/26/07	JoomlArt.com
4	rhuk_milkyway			1.0.2	11/20/06	Andy Miller

A dropdown menu at the bottom left says 'Display # 20'. In the toolbar at the top right, there are buttons for Preview, Logout, and other functions. A large yellow circle labeled '1' surrounds the second row in the table, and another large yellow circle labeled '2' surrounds the 'Default' button in the toolbar.

From the Template Manager page click on the template name you just installed and then click the Default button to make that template the default one.

Appendix B – How to setup a module

To setup a module in Joomla! 1.5.x follow the next 4 steps:


Step 1

Get into the administrator's control panel with your browser.

The URL usually looks like


<http://www.example.com/administrator/>

Step 2



Go to the menu Extensions > Module Manager


Step 3



Find the module you want to edit and click it.

Note: If you cannot find your module perhaps there are too many modules split in pages. Go through the pages to find your module, or use the filters to limit the list of modules on your screen.

Step 4



The screenshot shows the Joomla Module Editor interface. On the left, the 'Details' tab is active, displaying module configuration like Title, Show Title, Enabled, Position, Order, Access Level, ID, and Description. On the right, the 'Parameters' tab is active, showing settings for Target, Count, Banner Client, Category, Search By Tags, Randomise, Header Text, Footer Text, and Module Class Suffix. A yellow circle highlights the 'Save' button in the top right corner of the editor window.

Now you are in the page that controls the module.

From the Details area you can control many features including:

- Set the title of the module
- Show or hide the title
- Publish or unpublish the module by checking the Enabled attribute
- Set the position of the module

From the Parameters area you can control other features including the ability to

- Set the Module Class Suffix

To save your changes click the Save button ton the top right corner.

Appendix C - CMenus to Joomla! content link reference

To connect CMenus with the Joomla! content create an “External Link” menu item and use the “Link” text box to enter the connection command.

The following example will display the 10 latest articles:

```
:cnt:latest:max=10
```

Commands can take parameters. Type the colon (:) symbol before each parameter. Here is an example that demonstrates how you can build a link with multiple parameters:

```
:cnt:articles:cat=1,2,3:max=10:itemid=1
```

Available commands and their parameters:

C.1. articles

Displays article links in the order set from the control panel.

sec

Valid values: Comma separated list of the section IDs.

Description: When used, only the articles under the specified sections will appear.

Default: [none]

Example:

```
:cnt:articles:sec=1,2,3
```

cat

Valid values: Comma separated list of the category IDs.

Description: When used, only the articles under the specified categories will appear.

Default: [none]

Example:

```
:cnt:articles:cat=1,2,3
```

max

Valid values: Any positive integer number.

Description: Maximum number of items to display.

Default: 10

Example:

```
:cnt:articles:max=20
```

itemid

Valid values: Any positive integer number.

Description: Sets the "Itemid" URL variable. Joomla! needs this variable in order to understand which menu item is active.

Default: [none]

Example:

```
:cnt:articles:itemid=1
```

C.2. latest

Displays article links putting the newer ones first.

sec

Valid values: Comma separated list of the section IDs.

Description: When used, only the articles under the specified sections will appear.

Default: [none]

Example:

```
:cnt:latest:sec=1,2,3
```

cat

Valid values: Comma separated list of the category IDs.

Description: When used, only the articles under the specified categories will appear.

Default: [none]

Example:

```
:cnt:latest:cat=1,2,3
```

max

Valid values: Any positive integer number.

Description: Maximum number of items to display.

Default: 10

Example:

```
:cnt:latest:max=20
```

itemid

Valid values: Any positive integer number.

Description: Sets the "Itemid" URL variable. Joomla! needs this variable in order to understand which menu item is active.

Default: [none]

Example:

```
:cnt:latest:itemid=1
```

C.3. random

Displays article links in random order.

sec

Valid values: Comma separated list of the section IDs.

Description: When used, only the articles under the specified sections will appear.

Default: [none]

Example:

```
:cnt:random:sec=1,2,3
```

cat

Valid values: Comma separated list of the category IDs.

Description: When used, only the articles under the specified categories will appear.

Default: [none]

Example:

```
:cnt:random:cat=1,2,3
```

max

Valid values: Any positive integer number.

Description: Maximum number of items to display.

Default: 10

Example:

```
:cnt:random:max=20
```

itemid

Valid values: Any positive integer number.

Description: Sets the "Itemid" URL variable. Joomla! needs this variable in order to understand which menu item is active.

Default: [none]

Example:

```
:cnt:random:itemid=1
```

C.4. selected

Displays selected article links. Use the "id" parameter to set article IDs.

id

Valid values: Comma separated list of the article IDs.

Description: Defines the IDs of the articles to be displayed.

Default: [none]

Example:

```
:cnt:selected:id=1,2,3
```

sec

Valid values: Comma separated list of the section IDs.

Description: When used, only the articles under the specified sections will appear.

Default: [none]

Example:

```
:cnt:selected:id=1,2,3:sec=1,2,3
```

cat

Valid values: Comma separated list of the category IDs.

Description: When used, only the articles under the specified categories will appear.

Default: [none]

Example:

```
:cnt:selected:id=1,2,3:cat=1,2,3
```

max

Valid values: Any positive integer number.

Description: Maximum number of items to display.

Default: 10

Example:

```
:cnt:selected:id=1,2,3:max=20
```

itemid

Valid values: Any positive integer number.

Description: Sets the "Itemid" URL variable. Joomla! needs this variable in order to understand which menu item is active.

Default: [none]

Example:

```
:cnt:selected:id=1,2,3:itemid=1
```

Appendix D - CMenu to VirtueMart 1.1 link reference

To connect CMenu with VirtueMart's data create an "External Link" menu item and use the "Link" text box to enter the connection command.

The following example will display all the product categories:

```
:vm:subcategory
```

Commands can take parameters. Type the colon (:) symbol before each parameter. Here is an example that demonstrates how you can build a link with multiple parameters:

```
:vm:subcategory:id=1:depth=1:published=1:cur_vendor=0
```

Available commands and their parameters:

D.1. category

Displays product categories and their sub-categories.

id

Valid values: Comma separated list of product category IDs.

Description: When used, only the categories with the given IDs will appear.

Default: 0

Example:

```
:vm:category:id=1,2,3
```

depth

Valid values: Zero or any positive integer number.

Description: Value 1 or larger sets the maximum level of depth of the categories to appear. Value 0 shows them all.

Default: 0

Example:

```
:vm:category:depth=1
```

published

Valid values: 1 or 0 that represent published or all.

Description: Use value 1 if you want to list only the published categories, 0 if you want to list them all.

Default: 1

Example:

```
:vm:category:published=1
```

cur_vendor

Valid values: 1 or 0 that represent current vendor only, or all vendors.

Description: Use value 1 if you want to list the categories of the current vendor only, 0 if you want to list them all.

Default: 1

Example:

```
:vm:category:cur_vendor=1
```

D.2. subcategory

Displays product sub-categories.

id

Valid values: Comma separated list of the parent category IDs.

Description: When used, only the sub-categories of the given IDs will appear.

Default: 0

Example:

```
:vm:category:id=1,2,3
```

depth

Valid values: Zero or any positive integer number.

Description: Value 1 or larger sets the maximum level of depth of the categories to appear. Value 0 shows them all.

Default: 0

Example:

```
:vm:category:depth=1
```

published

Valid values: 1 or 0 that represent published or all.

Description: Use value 1 if you want to list only the published categories, 0 if you want to list them all.

Default: 1

Example:

```
:vm:category:published=1
```

cur_vendor

Valid values: 1 or 0 that represent current vendor only, or all vendors.

Description: Use value 1 if you want to list the categories of the current vendor only, 0 if you want to list them all.

Default: 1

Example:

```
:vm:category:cur_vendor=1
```

D.3. featured

Displays featured products.

max_items

Valid values: Any positive integer number.

Description: Maximum number of items to display.

Default: 10

Example:

```
:vm:featured:max_items=20
```

cat

Valid values: Comma separated list of category IDs.

Description: When used, only the products under the given categories will appear.

Example:

```
:vm:featured:cat=1,2,3
```

cur_vendor

Valid values: 1 or 0 that represent current vendor only, or all vendors.

Description: Use value 1 if you want to list products of the current vendor only, 0 if you want to list them all.

Default: 1

Example:

```
:vm:featured:cur_vendor=1
```

D.4. latest

Displays latest added products.

max_items

Valid values: Any positive integer number.

Description: Maximum number of items to display.

Default: 10

Example:

```
:vm:latest:max_items=20
```

cat

Valid values: Comma separated list of category IDs.

Description: When used, only the products under the given categories will appear.

Example:

```
:vm:latest:cat=1,2,3
```

cur_vendor

Valid values: 1 or 0 that represent current vendor only, or all vendors.

Description: Use value 1 if you want to list products of the current vendor only, 0 if you want to list them all.

Default: 1

Example:

```
:vm:latest:cur_vendor=1
```

D.5. random

Displays randomly selected products.

max_items

Valid values: Any positive integer number.

Description: Maximum number of items to display.

Default: 10

Example:

```
:vm:random:max_items=20
```

cat

Valid values: Comma separated list of category IDs.

Description: When used, only the products under the given categories will appear.

Example:

```
:vm:random:cat=1,2,3
```

cur_vendor

Valid values: 1 or 0 that represent current vendor only, or all vendors.

Description: Use value 1 if you want to list products of the current vendor only, 0 if you want to list them all.

Default: 1

Example:

```
:vm:random:cur_vendor=1
```

D.6. selected

Displays custom selected products.

id

Valid values: Comma separated list of product IDs.

Description: ID numbers of the products you want to show.

Example:

```
:vm:selected:id=1,2,3
```

The usage of the parameter id is compulsory.

D.7. topten

Displays best selling products.

max_items

Valid values: Any positive integer number.

Description: Maximum number of items to display.

Default: 10

Example:

```
:vm:topten:max_items=20
```

cat

Valid values: Comma separated list of category IDs.

Description: When used, only the products under the given categories will appear.

Example:

```
:vm:topten:cat=1,2,3
```

cur_vendor

Valid values: 1 or 0 that represent current vendor only, or all vendors.

Description: Use value 1 if you want to list products of the current vendor only, 0 if you want to list them all.

Default: 1

Example:

```
:vm:topten:cur_vendor=1
```



bonusthemes.com

E X T R E M E J O O M L A T E M P L A T I N G

Graphics: Mediagrafix - <http://www.mediagrafix.gr>
Programming: Creative Pulse - <http://www.creativepulse.eu>

Distribution - Support: <http://www.bonusThemes.com>